

TECHNICAL INFORMATION



Application:	Awning, Umbrella, Sunshade
Composition:	100% Solution-Dyed Acrylic
Finish:	Cleangard - Special treatment for dirt and water resistance
Weight:	295 g/m ²
Roll length:	60 m (65 yards)
Width:	120 cm (47") ₂
Water penetration resistance:	35 cm H O (≥ 13.8" H O)
Surface wetting resistance - Spray Test:	100 (max. 100)
Oil Repellency:	≥ 5
Tensile Strength (Warp/Weft):	130/75 daN per 5 cm (292/167 lbf per 2 in.)
Elongation at Break (Warp/Weft):	≤ 25% / ≤ 20%
Tear Strength (Warp/Weft):	5/3 daN (11.3/6.8 lbf per 2 in.)

Colour Fastness

To Artificial Light:	≥ 7 (Blue Scale, max. 8)
To Artificial Weathering:	≥ 7 (Blue Scale, max. 8)
To Seawater:	5 (max. 5)
To Chlorinated Water (Pools):	5 (max. 5)

Average values with a tolerance of +/- 5%. Non-binding information. Data based on tests carried out in our laboratories.

CARE&CLEAN



Maintenance guidelines: Remove dust using a vacuum cleaner without scrubbing. Clean with a sponge or soft brush dampened with water and mild soap.

WARRANTY

10 years

Made in Europe

This technical information applies to the following references of Acrilla:

001, 002, 004, 005, 010, 011, 012, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 128, 134, 135, 136, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 221, 224, 225, 264, 296, 308, 332, 367, 375, 379, 380, 438, 531, 532, 557, 560, 561, 562, 563, 566, 746, 843, 897, 898, 971 & 973.